

Selection Guide

Geotextile



	Applications	Functions						Main factors affecting the conception of the project	Proposed geotextile solutions			
		S	R	F	P	D	I		Intensity constraints at the site	Mechanical	Hydraulic	
Roads and Transportation	<p>Highways Roads (paved and unpaved) Boulevards Streets</p>	X	X	X		X	X ¹	Type of soil (mechanical / hydraulic) Soil support (Infrastructure) Granular foundation Density and type of traffic Mechanical stresses Structures present Projected life expectancy	Very low Low Medium High	TEXEL035C TEXEL045C TEXEL SX-60T Texel SX-90T Texel SX-130T	TEXEL080C TEXEL080E Texel Geo-9 R1	Texel Texdrain TEXEL PAVETEX SH¹ Texel DRAINTUBE
	<p>Parking lots Storage areas</p>	X	X	X		X	X ¹					
Natural Resources and Energy	<p>Riverbank protection Culverts Ditch channels Riprap protection Dikes and cofferdams</p>	X		X	X		Type of soil (mechanical / hydraulic) Mechanical stresses Hydraulic requirements Type of rockfill - medium: 0-30 cm - high: 30-100 cm - very high: >100 cm	Medium High Very High		TEXEL080C TEXEL100C TEXEL120C / TEXEL120E TEXEL160C / TEXEL160E TEXEL240E	Texel F-500	
	<p>Concrete structures Viaducts and bridge abutments Guardrails Weirs Slabs and decks</p>				X	X		Strength of concrete Aesthetic criteria Aggressiveness of the environment Climatic conditions and humidity	Low			Texel Texcure Texel Drainaform Texel Texdrain
Industrial and Waste Management	<p>Embedding sheaths Drainage trenches French / agricultural drains Edge drainage screens</p>	X		X		X	Type of soil (mechanical / hydraulic) Type of backfill Hydraulic requirements Liquid chemical composition Mechanical stresses	Low Medium	TEXEL035C TEXEL040C TEXEL045C	Texel F-909	Texel Filtex Texel F-200 Texel F-300 Texel Texdrain	
	<p>Leachate capture</p>	X		X		X						
	<p>Landfill cells Retention ponds Tailings ponds</p>		X		X	X		Type of backfill Type and grade of geomembrane Mechanical stresses	Medium High Very High		TEXEL080E TEXEL120E TEXEL240E	Texel DRAINTUBE
Municipal and Landscape Architecture	<p>Buildings Retaining walls Drainage under slab Green roofs</p>	X		X		X	Type of soil (mechanical / hydraulic) Hydraulic requirements Liquid chemical composition Mechanical stresses	Low Medium High		TEXEL080E TEXEL120E	Texel Texdrain Texel DRAINTUBE	
	<p>Sports fields Golf courses</p>	X		X		X	Type of soil (mechanical / hydraulic) Type of installation to be built Hydraulic requirements Mechanical stresses	Low Medium	TEXEL045C	TEXEL080C	Texel DRAINTUBE	
	<p>Landscape architecture Low walls Paving stones Pathways Bicycle paths</p>	X	X			X		Type of soil (mechanical / hydraulic) Type of installation to be built Hydraulic requirements Mechanical stresses	Very low Low	TEXEL035C TEXEL045C	Texel DRAINTUBE	

STANDARD PRODUCT WIDTHS

C SERIES	3.81 m / 4.57 m
TEXEL GEO-9 R1 & R2	4.00 m
E SERIES	3.81 m / 4.57 m
SX SERIES	3.81 m / 4.57 m / 5.33 m

CUTTING AND SEWING SERVICE

We offer, upon request, a cutting and sewing service to adjust the width of the rolls to the needs of your daily applications, as well as a daily rental of equipment for sewing and installation of many of our geosynthetics.

* SCALE OF CONSTRUCTABILITY REQUIREMENTS

	Low	Medium	High	Very High
Tensile Strength	400 to 500 N	500 to 1 000 N	1 000 to 1 550 N	More than 1 500 N
Elongation at break	150 to 250 N	250 to 400 N	400 to 800 N	More than 800 N
CBR puncture	1 000 to 1 550 N	1 550 to 2 500 N	2 500 to 5 000 N	More than 5 000 N

¹ The proposed solution for the waterproofing function is the Texel Pavetex SH.