

# TURBITEX

## TECHNICAL DATASHEET

<b>Geobarrier (GBR) type</b>	Turbidity barrier
<b>Composition</b>	Polypropylene / PVC
<b>Main function</b>	Protection

Property	Method	1-NTR	1-T <sup>(1)</sup>	1-CW	1-PVC 18	3-T	3-PVC 18	5-T	5-PVC 18
<b>Skirt</b>									
Composition	-	Reinforced nonwoven	Woven	Coated woven	PVC 18 oz	Woven	PVC 18 oz	Woven	PVC 18 oz
Tensile strength	ASTM D4632	650 N	1 400 N	453 N <sup>(2)</sup>	1 961 N <sup>(3)</sup>	1 400 N	1 961 N <sup>(3)</sup>	1 400 N	1 961 N <sup>(3)</sup>
Water flow rate	ASTM D4491	-	163 l/min/m <sup>2</sup>	Waterproof		163 l/min/m <sup>2</sup>	Waterproof	163 l/min/m <sup>2</sup>	Waterproof
Opening sizes (AOS)	ASTM D4751	40- 70 µm <sup>(4)</sup>	425 µm			425 µm		425 µm	
<b>Upper section</b>									
Floating material	-	Expanded polystyrene							
Float dimensions	-	6 pieces 10 cm X 10 cm X 244 cm				6 pieces 20 cm X 20 cm X 244 cm			
Buoyancy	ASTM D3575	9 kg/m				33 kg/m			
Float cover	-	12 mils coated woven				PVC 18 oz			
Color	-	Yellow							
Reinforcement strip	-	16 mils polyethylene coated woven				50 mm nylon strap			
UV resistance	ASTM G53	80% / 2000h							
<b>Accessories</b>									
Upper tension member	-	None (rope or steel cable available on request)			1 x 8 mm steel cable			2 x 8 mm steel cable	
Weight	-	8 mm grade 30 galvanized steel chain							
Eyelet	-	#3 plated brass or zinc							
Assembly	-	Knotted with nylon thread							
Connection	-	12 mm galvanized steel pin <sup>(5)</sup>							
<b>Standard sizes</b>									
Depth <sup>(6)</sup>	-	1 m - 2 m - 4 m - 6 m	1.2 m - 2.3 m - 3.3 m - 3.8 m - 5.8 m		1.3 m - 2.3 m - 3.0 m - 4.1 m - 5.0 m - 6.1 m				
Length <sup>(6)</sup>	-	15 m							

This technical information comes from the manufacturer and was transcribed by Texel.

1 - 1-NTR and 1-T, geotextile skirt for calm water applications in lakes and rivers with a velocity ≤ 1 ft/sec / 2 - According to ASTM D751 / 3 - According to FS5134

4 - FOS according to CAN/CGSB 148.1 No.10.2 / 5 - Possibility of connectors meeting ASTM F2438 / 6 - Possibility of custom sizes

Revision : 2023-09-28

Texel reserves the right to modify existing properties contingent on the evolution of technical knowledge. Each user is invited to verify if this document represents the most recent update. Texel offers no guarantee and assumes no responsibility regarding usage, installation and/or convenience of usage. Texel must be informed of all product defects or product nonconformity prior to installation. Responsibility is limited to replacement of non-compliant or defective product.