

TECHNICAL DATA SHEET

TM300 SERIES



Product	Bituminous geomembrane
Composition	Geocomposite
Main Function	Waterproofing

Property	Test Method	Texel ES1		Texel ES2		Texel ES3	
		Typical	Minimum	Typical	Minimum	Typical	Minimum
Physical							
Geocomposite							
Glass mat	-	50 g/m ²		50 g/m ²		50 g/m ²	
Non-woven geotextile		200 g/m ²		250 g/m ²		300 g/m ²	
Elastomeric SBS		3800 g/m ²		4300 g/m ²		4800 g/m ²	
Sand		250 g/m ²		250 g/m ²		250 g/m ²	
Polyester		15 g/m ²		15 g/m ²		15 g/m ²	
Weight	ASTM D3776	4.20 kg/m ²	3.70 kg/m ²	4.85 kg/m ²	4.30 kg/m ²	5.80 kg/m ²	5.00 kg/m ²
Thickness	ASTM D5199	3.50 mm	3.10 mm	4.00 mm	3.60 mm	4.80 mm	4.20 mm
Mechanical							
Tear strength (MD/CD)	ASTM D4073	750 / 500 N	563 / 375 N	825 / 700 N	619 / 525 N	950 / 850 N	713 / 638 N
Tensile strength (MD/CD)	ASTM D7275	22 / 18 kN/m	16.5 / 13.5 kN/m	27 / 24 kN/m	20.3 / 15 kN/m	33 / 29 kN/m	24.8 / 21.8 kN/m
Elongation at break (MD/CD)	ASTM D7275	60 / 45%					
Puncture resistance	ASTM D4833	450 N	405 N	530 N	477 N	570 N	513 N
Flexibility at low temperature	ASTM D5147	-20 / -15 °C					
Hydraulic							
Water vapor transmission rate	ASTM E96	< 6 x 10 ⁻¹⁴ m/s					
Gas permeability	ASTM D1434	< 2 x 10 ⁻¹⁴ m ³ /(m ² ·j·amt)					
Dimensions							
Width	-	5.1 m	5.01 m	5.1 m	5.01 m	5.1 m	5.01 m
Length	-	100 m	99 m	80 m	79 m	65 m	64 m

This technical information comes from the manufacturer and was transcribed by Texel. Texel TM300 ES4 also available on request.
 Rolls must not be stored directly on the ground. They must be laid supported on concrete blocks, trestles or timber beams min 35cm/1.2 ft height, placed under the mandrel ends.

Revision : 2020-04-27

Texel reserves the right to modify existing properties contingent on the evolution of technical knowledge. Each user is invited to verify if this document represents the most recent update. Texel offers no guarantee and assumes no responsibility regarding usage, installation and/or convenience of usage. Texel must be informed of all product nonconformity prior to installation. Responsibility is limited to replacement of non-compliant or defective product.

